

TIMPANI SQ™ - SUSPENDED



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

973020 24", Direct, 4991 lms Direct	973030 36", Direct, 13279 lms Direct	973040 48", Direct, 25532 lms Direct	973120 24", Direct/Indirect, 4983 lms Direct, 3575 lms Indirect
973130 36", Direct/Indirect, 13285 lms Direct, 7153 lms Indirect	973140 48", Direct/Indirect, 25584 lms Direct, 7118 lms Indirect		

Recommended minimum suspension length: 12" for White LEDs, 24" for Colored LEDs

B. CCT/COLOR (DIRECT)

D30 3000K (min 80 CRI)	D35 3500K (min 80 CRI)	D40 4000K (min 80 CRI)
-------------------------------	-------------------------------	-------------------------------

C. CCT/COLOR (INDIRECT)

N30 3000K (min 80 CRI) NGN Green	N35 3500K (min 80 CRI) NBL Blue	N40 4000K (min 80 CRI)	NRD Red
---	--	-------------------------------	----------------

D. FINISH

WH White	BL Black Metallic Textured	MS Silver Metallic Textured	FA44 Midnight Blue Metallic - Textured
FA25 Gold Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

E. LUMEN & WATTAGE REDUCTION

PRO Lumen & Wattage Reduction to approximately 25% of standard output	PR1 Lumen & Wattage Reduction to approximately 50% of standard output	PR2 Lumen & Wattage Reduction to approximately 75% of standard output
--	--	--

Note: Custom Reduction Percentages Available Upon Request.

F. DIMMING OPTIONS

D1 0-10V Dimming (1%)	D2 0-10V Dimming 0.1% ¹	DL DALI Dimming (1%)	DS DSI (EU only) ²
SD SwitchDim (EU only) ²	DE PoE ³		

0-10V, 1% dimming standard.

¹ available with 24" (610mm) diameters only.

² DS & SD options not available in North America.

³ DE must be used with EV only.

G. OPTIONS

EM Integral Emergency	EN Encelium/Zigbee Control	OD Opal diffuser for uplight (10% reduction on Indirect lms)	SS Separate Switching (two power cables supplied)
------------------------------	-----------------------------------	---	--

H. OPTIONAL LOW VOLTAGE

EV Low Voltage

To be used with DE only.



TIMPANI SQ™ - SUSPENDED

DIMENSIONAL DIAGRAMS

S1 - Vertical suspension

