





# TRILOGY CRADLE™


## FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

### 1 DESCRIPTION

### 2 OPTICS & FEATURES



Ceiling  
Direct/Indirect

### 3 APPROVALS



### 4 GENERAL SPECIFICATION

#### BODY AND TRIM

Steel and aluminum.

#### LENS

Three ply satin opal glass.

#### FINISH

Back plate, powder coated gloss white. Trim, painted or plated as listed.

#### DRIVERS

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

**LUMINAIRE ORIENTATION**

Ceiling or wall mounted.

**MECHANICAL**

Mounts directly to a junction box (by others - North America only).

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**APPROVALS**

Damp Location (Indoor use only).

**5 HOW TO ORDER**

LUMINAIRE	CCT	FINISH
<b>638818</b> 63 8818	<b>30</b> 3000K (min 80 CRI) <b>35</b> 3500K (min 80 CRI) <b>40</b> 4000K (min 80 CRI)	<b>WH</b> White <b>MB</b> Metallic Bronze <b>MS</b> Silver Metallic <b>PC</b> Polished Chrome <b>SC</b> Satin Chrome <b>SN</b> Satin Nickel <b>OT</b> Other painted finish (RAL number required) <b>F40</b> Other Non-RAL painted finish (sample chip required) OT & BL1 have a one time set-up charge regardless of quantity.

**6 TECHNICAL DATA**

**LUMINAIRE**

<b>Code</b>	<b>638818</b>
<b>Power (LED)</b>	21W
<b>Delivered lms</b>	1240
<b>LPW</b>	59
<b>Weight</b>	6.3Kg/14lb

**7** DIMENSIONAL DIAGRAMS

