

TRILOGY CRADLE™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



TRILOGY CRADLE™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Back plate, powder coated gloss white. Trim, painted or plated as listed.

Diffuser

Three ply satin opal glass.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall mounted.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



Ceiling Direct/Indirect

TRILOGY CRADLE™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

638818 63 8818

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MB Metallic Bronze

MS Silver Metallic

PC Polished Chrome

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	638818
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	6.3Kg/14lb

APPROVALS



TRILOGY CRADLE™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

