Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Lens

Three ply satin opal glass.

Luminaire orientation

Ceiling or wall mounted.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Trim, painted or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling Direct/Indirect

HOW TO ORDER

A. LUMINAIRE

638818 63 8818

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

MS Silver Metallic

C. FINISH

WH White MB Metallic Bronze **SC** Satin Chrome **SN** Satin Nickel

OT Other painted finish (RAL number required)

PC Polished Chrome

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code 638818 Power (LED) 21W **Delivered Ims** 1240 LPW 59 Weight 6.3Kg/14lb

APPROVALS













DIMENSIONAL DIAGRAMS

