Fixture Code:	Quantities:
Project Name:	Fixture Type:



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Lens

Three ply satin opal glass.

Luminaire orientation

Ceiling or wall mounted.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Trim, painted or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES





Ceiling Direct/Indirect

Direct-indirect

HOW TO ORDER

A. LUMINAIRE

638860 21W, 1240 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White BM Bronze Metallic Textured MS Silver Metallic PC Polished Chrome

SC Satin Chrome SN Satin Nickel F39 Other painted finish (RAL number required) F40 Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	638860
Power (LED)	21W
Delivered Ims	1240
LPW	59
Weight	14lb

APPROVALS













DIMENSIONAL DIAGRAMS

