Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Aluminium and steel.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Suspension

Three cables.

Lens

Hand blown, triple ply, satin opal glass.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct/Indirect

HOW TO ORDER

A. LUMINAIRE

639810 639810

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. FINISH

MS Silver Metallic **PC** Polished Chrome **SC** Satin Chrome **SN** Satin Nickel

OT Other painted finish (RAL number F40 Other Non-RAL painted finish

required) (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. OPTIONS

CB Cradle Bars **HR** Halo Rings

TECHNICAL DATA

LUMINAIRE

Code 639810 Power (LED) 21W LED **Delivered Ims** 1240 LPW 59

APPROVALS











DIMENSIONAL DIAGRAMS

