

TRILOGY™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



TRILOGY™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Aluminium and steel.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Suspension

Three cables.

Lens

Hand blown, triple ply, satin opal glass.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct/Indirect

TRILOGY™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

639810 639810

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

MS Silver Metallic

PC Polished Chrome

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. OPTIONS

HR Halo Rings

CB Cradle Bars

TECHNICAL DATA

LUMINAIRE

Code	639810
Power (LED)	21W LED
Delivered lms	1240
LPW	59

APPROVALS



TRILOGY™ - SUSPENDED

DIMENSIONAL DIAGRAMS

