

# TRILOGY™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# TRILOGY™ - CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Back plate, powder coated gloss white.

### Lens

Three ply satin opal glass.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

### Luminaire orientation

Ceiling or wall mounted.

### Mechanical

Mounts directly to a junction box (by others - North America only).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


### Approvals

Damp Location (Indoor use only).

## OPTICS & FEATURES



Ceiling Direct/Indirect



Direct-indirect

# TRILOGY™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**635220** 21W, 1240 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>635220</b>
<b>Power (LED)</b>	21W
<b>Delivered lms</b>	1240
<b>LPW</b>	59
<b>Weight</b>	14lb

---

## APPROVALS



DAMP  
LOCATION



IP20



# TRILOGY™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

