

# TRILOGY™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# TRILOGY™ - CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Finish**

Back plate, powder coated gloss white.

**Diffuser**

Three ply satin opal glass.

**Drivers**

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

**Luminaire orientation**

Ceiling or wall mounted.

**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**Approvals**

Damp Location (Indoor use only).

## OPTICS & FEATURES



Ceiling Direct/Indirect



Direct-indirect

# TRILOGY™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**635220** 21W, 1240 lms

### B. CCT

**30** 3000K (min 80 CRI)                      **35** 3500K (min 80 CRI)                      **40** 4000K (min 80 CRI)

## TECHNICAL DATA

### LUMINAIRE

Code	<b>635220</b>
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	14lb

## APPROVALS



# TRILOGY™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

