

TRILOGY™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



TRILOGY™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Back plate, powder coated gloss white.

Lens

Three ply satin opal glass.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall mounted.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling Direct/Indirect



Direct-indirect

TRILOGY™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

635220 21W, 1240 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

TECHNICAL DATA

LUMINAIRE

Code	635220
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	14lb

APPROVALS



DAMP
LOCATION



IP20



TRILOGY™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

