


TUNNEL™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

TLCC1C Direct, 1300 lms/ft

All data shown at max values based on diffused light diffuser. Consult Performance Data download page for more detail.
One power cord for every 50 linear feet.

B. LENGTH OF RUN

SFA _ _ _ _

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run. For 6 inch increments, consult factory.

C. LENGTH

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

Length of run is 4, 6, 8, 10 or 12 feet only, not available as a continuous run.

D. LM/FT

LPF020 200 lm/ft

LPF040 400 lm/ft

LPF060 600 lm/ft

LPF080 800 lm/ft

LPF100 1000 lm/ft

LPF120 1200 lm/ft

LPF140 1400 lm/ft

E. CRI

CR80 CRI 80+

CR90 CRI 90+

F. CCT

CTA30 3000K

CTA35 3500K

CTA40 4000K

G. DIFFUSER

DD1 Asymmetric diffuser ¹

DD2 Batwing diffuser

DD3 Diffused light diffuser ^{1 2}

DD4 Comfort diffuser ³

¹ When standing at the end view of the profile on the side where the power cord is installed, the asymmetric beam will aim to the right.

² High output diffuser, all data shown based on this diffuser.

³ 10% reduction from DD3. The comfort lens provides better control and softer distribution.

H. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Only available with DA01 dimming.



TUNNEL™ - CEILING

I. DIMMING

DA01 0-10V Dimming 1.0%
DA30 DSI/switchDim ²

DA02 0-10V Dimming 0.1% ¹
DA45 PoE ³

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

¹ Not available with V3.

² Not available in North America.

³ Only available with V4.

J. FINISH

FA01 White - Textured

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry ¹

FA28 Wood grain - Dark Walnut ¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

K. EMERGENCY

E0 Not required

E1 Emergency system - Integral ¹


E3 Emergency generated circuit ¹

¹ Not available with 347V.




TUNNEL™ - CEILING

DIMENSIONAL DIAGRAMS



ISOMETRIC BOTTOMVIEW



Bottom View

Top View
(Asymmetric Light Direction)

