TUNNEL QUAD™

FULL SPECIFICATION SHEET



FIXTURE TYPE	FIXTURE CODE	QUANTITIES

1 DESCRIPTION


TUNNEL revives the classic functional form into a charming new style with an incurved enhancement. With this design flair comes great functionality. **TUNNEL** exceeds typical levels of output and efficacy, and delivers on specification capabilities. Its 13 luxurious finishes and smooth lines create a stylish luminaire that doesn't compromise on performance. These fixtures are BIOS and Tunable White compatible, ensuring optimal visual comfort.

2 OPTICS & FEATURES


Suspended Direct


Suspended Direct/Indirect


Direct DD2


Direct DD4


Indirect UD1



Bios



Declare



PoE



Tunable White

3 APPROVALS



4 GENERAL SPECIFICATION

BODY
Aluminum.

FINISH
Powder coated.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

SUSPENSION
Steel cables.

POWER CABLE
Silver braided.

POE
Can be integrated into your data network via Power over Ethernet (PoE) connectivity.

BIOS
For circadian lighting, consult factory.

TUNABLE WHITE
Tunable White range from 2700K to 6500K is available; contact the factory for details.

RGBW
RGBW available, consult factory.

DRIVERS
HPF electronic drivers for 120-277V, 347 (EU-240V). The driver is integral to the fixture housing.

LENS
Opal acrylic. 2.4" width

DELIVERED LUMENS
Delivered lumens & LPW based on 4000K CRI 80+

MECHANICAL
Luminaires mount directly over J box (by others).

FIXTURE LENGTHS
Available in 1" increments. Contact the factory for details.

REPORTED L70 @25°C (77°F)
> 60,000 hrs @ 2000 lumens/ft (6000 lumens/m)

ESTIMATED L70 @25°C (77°F)
> 165,000 hrs @ 2000 lumens/ft (6000 lumens/m)

INTEGRAL EMERGENCY SYSTEM (E1)
Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply. Refer to the Emergency option notes below for wattage, configuration and regional details.

LUMINAIRE LEVEL LIGHTING CONTROLS
This product can be configured for integration with luminaire-level lighting controls. Contact the factory for available options and project-specific requirements.

APPROVALS
Damp Rated.

DESIGN
US Design Patent Pending.

SEISMIC BRACING
Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

SUSTAINABILITY
Designed for on-site LED board, driver, and optic replacement. Contact the factory for maintenance documentation.

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

5 DESIGN OPTIONS

FIXTURE FINISH

White - Textured


Black Metallic - Textured



Silver Metallic - Textured


Gold Metallic - Textured



Wood grain - Light Cherry [1]


Wood grain - Dark Walnut [1]


Wood grain - White Oak [1]


Midnight Blue Metallic - Textured


Copper Metallic


Charcoal Metallic - Textured


Bronze Metallic - Textured


Champagne Metallic


Red Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.


CANOPY FINISH

White



Black Metallic - Textured


Silver Metallic - Textured


Gold Metallic - Textured


Midnight Blue Metallic - Textured


Copper Metallic


Charcoal Metallic - Textured


Bronze Metallic - Textured


Champagne Metallic


Red Metallic - Textured

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

6 HOW TO ORDER

LUMINAIRE

TLCQ1P01 27.2" Sq, Direct
TLCQ1P02 51.2" Sq, Direct
TLCQ1P05 27.20" x 51.20", Direct
TLCQ2P01 27.2" Sq, Direct/Indirect
TLCQ2P02 51.2" Sq, Direct/Indirect
TLCQ2P05 27.2" x 51.2", Direct/Indirect

For larger sizes, refer to Tunnel Systems. One power cord for every 50 linear feet.

LUMENS/FT (DIRECT)

LPF020 200 lm/ft
LPF040 400 lm/ft
LPF060 600 lm/ft
LPF080 800 lm/ft
LPF100 1000 lm/ft
LPF120 1200 lm/ft
LPF140 1400 lm/ft

LUMENS/FT (INDIRECT)

LPG000 Not required
LPG020 200 lm/ft
LPG040 400 lm/ft
LPG060 600 lm/ft
LPG080 800 lm/ft
LPG100 1000 lm/ft
LPG120 1200 lm/ft
LPG140 1400 lm/ft
LPG165 1650 lm/ft

CRI

CR80 CRI 80+
CR90 CRI 90+

CCT DIRECT

CTA27 2700K
CTA30 3000K
CTA35 3500K
CTA40 4000K
CTA60 Tunable White

* If Tunable White is required, it needs to be selected for both direct and indirect. For other combinations, consult factory.

CCT INDIRECT

CTB00 Not required
CTB27 2700K
CTB30 3000K
CTB35 3500K
CTB40 4000K
CTB60 Tunable White

* If Tunable White is required, it needs to be selected for both direct and indirect. For other combinations, consult factory.

DIRECT LENS

DD2 Batwing
DD4 Comfort

INDIRECT LENS (BATWING)

UD0 Not required
UD4 Extra Wide Batwing [1]
UD1 Batwing

[1] Available up to 1400 lm/ft.

UPLIGHT BLACKOUT PLATE

UB00 Not required
UB_ _ Blackout plate [1]

[1] Available on a per foot basis. May be required to prevent lighting up of duct work in loft style applications.

VOLTAGE

V1 120/277V
V2 240V [1]
V3 347V [2]
V4 Low Voltage [3]

[1] Not available in North America. [2] Only available with DA01 dimming.

DIMMING

DA01 0-10V Dimming 1.0%
DA02 0-10V Dimming 0.1% [1]
DA20 DALI Dimming 0.1% [1]
DA21 DALI Dimming 1.0% [1]
DA23 DALI DT8 Dimming 0.1% - Tunable White [1] [2]
DA45 PoE [3]

[1] Not available with V3.
[2] Only available with Tunable White.
[3] Only available with V4.

CEILING TYPE

G1 Grid ceiling [1]
H1 Hard ceiling [2]

The cost for the canopies, power cables, connections mechanisms and endcaps for the fixture has been added to these items.
[1] Combo kit provided includes installation to T-bar and through tile mount. [2] Designed for drywall ceilings.

SUSPENSION

HLA03 3ft cable suspension
HLA06 6ft cable suspension
HLA09 9ft cable suspension

FIXTURE FINISH

FA01 White - Textured
FA02 Black Metallic - Textured
FA20 Silver Metallic - Textured
FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry [1]
FA28 Wood grain - Dark Walnut [1]
FA30 Wood grain - White Oak [1]
FA44 Midnight Blue Metallic - Textured
FA45 Copper Metallic
FA46 Charcoal Metallic - Textured
FA47 Bronze Metallic - Textured
FA52 Champagne Metallic
FA53 Red Metallic - Textured

[1] Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

CANOPY FINISH

CF01 White
CF02 Black Metallic - Textured
CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured
CF45 Copper Metallic
CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured
CF52 Champagne Metallic
CF53 Red Metallic - Textured

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

EMERGENCY

E0 Not required

E1 Emergency system - Integral [1]

E3 Emergency generated circuit [1]

[1] For North America, the minimum emergency system wattage is 10W. Refer to the fixture's lumens per watt to estimate emergency light output. The emergency system typically powers only a portion of the fixture, depending on the fixture configuration and number of drivers. Consult factory for emergency system configuration and illuminated section details.
For Europe, the emergency system wattage and configuration may vary. Consult factory for details.

CIRCUITS

CS1 Single circuit

CS2 Dual circuit [1]

SENSORS

This product can be configured for integration with luminaire-level lighting controls. Contact the factory for available options and project-specific requirements.


7 TECHNICAL DATA


LUMINAIRE


For larger sizes, refer to Tunnel Systems. One power cord for every 50 linear feet.

Code	TLCQ1P01	TLCQ1P02	TLCQ1P05	TLCQ2P01	TLCQ2P02	TLCQ2P05
Light Direction						

8 PERFORMANCE DATA

DIRECT COMFORT (DD4)	LUMEN/FT	WATT/FT	LPW
	1400	13	103
	1200	11	106
	1000	9	109
	800	7	112
	600	5	115
	400	3	119
	200	2	120


DIRECT BATWING (DD2)	LUMEN/FT	WATT/FT	LPW
	1400	13	108
	1200	11	112
	1000	9	115
	800	7	118
	600	5	121
	400	3	124
	200	2	129

INDIRECT BATWING (UD1)	LUMEN/FT	WATT/FT	LPW
	1650	13	132
	1400	10	137
	1200	9	140
	1000	7	144
	800	6	146
	600	4	150
	400	3	153
	200	1	153

© 2026 Beta-Calco Inc. Specifications are subject to change without notice


9 TM-30 DATA

CCT 2700K




CRI(Ra)	93
CRI(R9)	61
TM30(Rf)	91
TM30(Rg)	98
Duv	-0.0022

CCT 3000K




CRI(Ra)	92
CRI(R9)	58
TM30(Rf)	92
TM30(Rg)	100
Duv	-0.0003

CCT 3500K



CRI(Ra)	91
CRI(R9)	53
TM30(Rf)	90
TM30(Rg)	99
Duv	-0.0007


CCT 4000K




CRI(Ra)	93
CRI(R9)	64
TM30(Rf)	90
TM30(Rg)	98
Duv	0.0000


© 2026 Beta-Calco Inc. Specifications are subject to change without notice

10 DIMENSIONAL DIAGRAMS





ISOMETRIC BOTTOM VIEW



Luminaire	A	B
TLCQ1P01/TLCQ2P01	27 3/16" [690mm]	27 3/16" [690mm]
TLCQ1P02/TLCQ2P02	51 3/16" [1300mm]	51 3/16" [1300mm]
TLCQ1P05/TLCQ2P05	27 3/16" [690mm]	51 3/16" [1300mm]

© 2026 Beta-Calco Inc. Specifications are subject to change without notice