

# WARP™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

## A. LUMINAIRE

**WARC1P18** 18", 3300 lms

**WARC1P24** 24", 4900 lms

## B. LUMENS

**LMA0200** 2000 lm

**LMA0330** 3300 lm

**LMA0490** 4900 lm

<sup>1</sup> Available for WARC1P24 only.

## C. CRI

**CR80** CRI 80+

## D. CCT

**CTA27** 2700K

**CTA30** 3000K

**CTA35** 3500K

**CTA40** 4000K

## E. VOLTAGE

**V1** 120/277V

**V2** 240V <sup>1</sup>

**V3** 347V <sup>2</sup>

<sup>1</sup> Not available in North America.

<sup>2</sup> Available with DA01 dimming only.

## F. DIMMING

**DA01** 0-10V Dimming 1.0%

**DA02** 0-10V Dimming 0.1% <sup>1</sup>

**DA20** DALI Dimming 0.1% <sup>1</sup>

**DA21** DALI Dimming 1.0% <sup>1</sup>

**DA30** DSI/switchDim <sup>1 2</sup>

<sup>1</sup> Not available with V3.

<sup>2</sup> Not available in North America.

## G. FINISH

**FA01** White

**FA02** Black Metallic - Textured

**FA20** Silver Metallic - Textured

**FA25** Gold Metallic - Textured

**FA44** Midnight Blue Metallic - Textured

**FA45** Copper Metallic

**FA46** Charcoal Metallic - Textured

**FA47** Bronze Metallic - Textured

**FA52** Champagne Metallic

**FA53** Red Metallic - Textured

## H. EMERGENCY

**E0** Not required

**E1** Emergency system - Integral

**E2** Emergency system - Remote

## I. DOWNLIGHT SPOT

**DL00** Not required

**DL27** Downlight 28W, 2700K (1730 delivered lms)

**DL30** Downlight 28W, 3000K (1799 delivered lms)

**DL35** Downlight 28W, 3500K (1854 delivered lms)

**DL40** Downlight 28W, 4000K (1858 delivered lms)

Beam angle for Downlight Spot is 40°.

## CIRCUITS

**CS1** Single Circuit

**CS2** Dual Circuit



# WARP™ - CEILING

## DIMENSIONAL DIAGRAMS

