

WARP™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

WARC1P18 18", 3300 lms

WARC1P24 24", 4900 lms

B. LUMENS

LMA0200 2000 lm

LMA0330 3300 lm

LMA0490 4900 lm

¹ Available for WARC1P24 only.

C. CRI

CR80 CRI 80+

D. CCT

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

¹ Not available in North America.

² Available with DA01 dimming only.

F. DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1% ¹

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

DA30 DSI/switchDim ^{1 2}

¹ Not available with V3.

² Not available in North America.

G. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

H. EMERGENCY

E0 Not required

E1 Emergency system - Integral

E2 Emergency system - Remote

I. DOWNLIGHT SPOT

DL00 Not required

DL27 Downlight 28W, 2700K (1730 delivered lms)

DL30 Downlight 28W, 3000K (1799 delivered lms)

DL35 Downlight 28W, 3500K (1854 delivered lms)

DL40 Downlight 28W, 4000K (1858 delivered lms)

Beam angle for Downlight Spot is 40°.

CIRCUITS

CS1 Single Circuit

CS2 Dual Circuit



WARP™ - CEILING

DIMENSIONAL DIAGRAMS

