

WINDSOR™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



WINDSOR™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Lens

Opal or faux alabaster acrylic.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming

Luminaire orientation

Ceiling mounted.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

WINDSOR™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

606001 606001

606011 606011

606014 606014

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. LENS

OP Opal Acrylic

FB Beige Faux Alabaster

FW White Faux Alabaster

D. FINISH

MB Metallic Bronze

MS Silver Metallic

AB Antique Brass

PB Polished Brass

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

| Code | 606001 | 606011 | 606014 |
|---------------|--------|--------|--------|
| Power (LED) | 28W | 28W | 36W |
| Delivered lms | 1715 | 1978 | 2616 |
| LPW | 63 | 71 | 72 |
| Diameter (A) | 18" | 24" | 24" |
| Weight | 8.1lb | 9.9lb | 9.9lb |

APPROVALS



WINDSOR™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

