WINDSOR™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

WINDSOR™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim
Steel and aluminum.

Finish
Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Lens
Opal or faux alabaster acrylic.

Drivers
HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming

Luminaire orientation
Ceiling mounted.

Mechanical
Mounts directly to a junction box (by others - North America only).

Delivered Lumens
Delivered lumens & LPW based on 4000K (min 80 CRI).

Approvals
Damp Location (Indoor use only).

OPTICS & FEATURES



Surface

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

WINDSOR™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

606001 606001

606011 606011

606014 606014

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. LENS

OP Opal Acrylic

FB Beige Faux Alabaster

FW White Faux Alabaster

D. FINISH

MB Metallic Bronze

MS Silver Metallic

AB Antique Brass

PB Polished Brass

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE


Code	606001	606011	606014
Power (LED)	28W	28W	36W
Delivered lms	1715	1978	2616
LPW	63	71	72
Diameter (A)	18"	24"	24"
Weight	8.1lb	9.9lb	9.9lb

APPROVALS

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

WINDSOR™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS



© 2026 Beta-Calco Inc. Specifications are subject to change without notice