Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Finish

Steel and aluminum. Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Lens

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming Opal or faux alabaster acrylic.

Luminaire orientation Mechanical

Ceiling mounted. Mounts directly to a junction box (by others - North America only).

Drivers

Delivered Lumens Approvals

Delivered lumens & LPW based on 4000K (min 80 CRI). Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

HOW TO ORDER

A. LUMINAIRE

606001 606001 **606011** 606011 **606014** 606014

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. LENS

OP Opal Acrylic FB Beige Faux Alabaster FW White Faux Alabaster

D. FINISH

MB Metallic Bronze MS Silver Metallic **AB** Antique Brass **PB** Polished Brass

SB Satin Brass **SC** Satin Chrome **SN** Satin Nickel **OT** Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	606001	606011	606014
Power (LED)	28W	28W	36W
Delivered Ims	1715	1978	2616
LPW	63	71	72
Diameter (A)	18"	24"	24"
Weight	8.1lb	9.9lb	9.9lb

APPROVALS













DIMENSIONAL DIAGRAMS

