

WINDSOR™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



WINDSOR™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Diffusers

Opal or faux alabaster acrylic.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming

Luminaire orientation

Ceiling mounted.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

WINDSOR™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

606001 606001	606011 606011	606014 606014
----------------------	----------------------	----------------------

B. CCT

30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------	------------------------------

C. DIFFUSER

OP Opal Acrylic	FB Beige Faux Alabaster	FW White Faux Alabaster
------------------------	--------------------------------	--------------------------------

D. FINISH

MB Metallic Bronze	MS Silver Metallic	AB Antique Brass	PB Polished Brass
SB Satin Brass	SC Satin Chrome	SN Satin Nickel	OT Other painted finish (RAL number required)
F40 Other Non-RAL painted finish (sample chip required)			

OT & BL 1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	606001	606011	606014
Power (LED)	28W	28W	36W
Delivered lms	1715	1978	2616
LPW	63	71	72
Diameter (A)	18"	24"	24"
Weight	8.1lb	9.9lb	9.9lb

APPROVALS



WINDSOR™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

