

WINDSOR™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



WINDSOR™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffuser

Opal acrylic.

Drivers

HPF electronic, 120-277V (EU-240V), 0-10V, 1% dimming standard.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Cover, finished as listed.


Dust covers

Opal dust cover standard.

Mechanical

Luminaires mount directly to a junction box. (by others - North America Only).

MOUNTING & OPTICS



Wall Front/Back



WINDSOR™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

591110 591110

591141 591141

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. DIFFUSER

OP Opal

FB Beige faux alabaster

FW White faux alabaster

D. FINISH

MB Metallic Bronze

MS Silver Metallic

AB Antique Brass

PB Polished Brass

SB Satin Brass

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	591110	591141
Power (LED)	14W	32W
Delivered lms	940	2120
LPW	64	69
Height (A)	13"	24"
Width (B)	8.5"	10"
Weight	9lb	18lb

APPROVALS



WINDSOR™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

