

# WINDSOR™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# WINDSOR™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and brass.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Mechanical

Luminaires mount directly over a junction box (by others- North America only).

### L70 @25°C (77°F)

>50,000 hrs.

### Suspension

Single tube combined with three diagonal decorative tubes for stabilization.

### Diffusers

Acrylic.

### Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Suspended Direct/Indirect



Direct-indirect



# WINDSOR™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**607010** 24", 12714 lms

**607020** 30", 15439 lms

**607030** 35", 22743 lms

**607040** 46", 30973 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BM** Bronze Metallic Textured

**MS** Silver Metallic

**AB** Antique Brass

**PB** Polished Brass

**SB** Satin Brass

**SC** Satin Chrome

**SN** Satin Nickel

**F39** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish (sample chip required)

---

F39 & F40 have a one time set-up charge regardless of quantity.

### D. DIFFUSER

**OP** Opal

### E. DIMMING

**DA** DALI Drivers

**DX** DMX Drivers

### F. ADDITIONAL SUSPENSION LENGTHS

**S1** 6" additional suspension length

**S2** 12" additional suspension length

**S3** 18" additional suspension length

**S4** 24" additional suspension length

### G. OPTIONS

**RE** Remote Emergency (max distance 10 ft., 120/277V)

**SW** Swivel Canopy (42 )



# WINDSOR™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

Code	607010	607020	607030	607040
Power	128W	150W	212W	283W
Delivered lms	12714	15439	22743	30973
LPW	100	104	107	109
Diameter (A)	24"	30"	35"	46"
Diameter (B)	5.3"	5.3"	5.3"	8.0"
Height (H)	20"	21"	21"	24"
Height (A)	3.9"	3.9"	3.9"	2.0"
Depth (D)	9"	9"	15"	18"
Weight	29lbs	33lbs	46lbs	84lbs

---

## APPROVALS



IP20



# WINDSOR™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

