

WINDSOR™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 5

WINDSOR™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and brass.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Mechanical

Luminaires mount directly over a junction box (by others- North America only).

Suspension

Single tube combined with three diagonal decorative tubes for stabilization.

Lens

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

L70 @25°C (77°F)

>50,000 hrs.


Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect



WINDSOR™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

607010 24", 12714 lms

607020 30", 15439 lms

607030 35", 22743 lms

607040 46", 30973 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BM Bronze Metallic Textured

MS Silver Metallic

AB Antique Brass

PB Polished Brass

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

F39 Other painted finish (RAL number required)

F40 Other Non-RAL painted finish
(sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. DIMMING

DA DALI Drivers

DX DMX Drivers

F. ADDITIONAL SUSPENSION LENGTHS

S1 6" additional suspension length

S2 12" additional suspension length

S3 18" additional suspension length

S4 24" additional suspension length

G. OPTIONS

RE Remote Emergency (max distance
10 ft., 120/277V)

SW Swivel Canopy (42°)



WINDSOR™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	607010	607020	607030	607040
Power	128W	150W	212W	283W
Delivered lms	12714	15439	22743	30973
LPW	100	104	107	109
Diameter (A)	24"	30"	35"	46"
Diameter (B)	5.3"	5.3"	5.3"	8.0"
Height (H)	20"	21"	21"	24"
Height (A)	3.9"	3.9"	3.9"	2.0"
Depth (D)	9"	9"	15"	18"
Weight	29lbs	33lbs	46lbs	84lbs

APPROVALS



WINDSOR™ - SUSPENDED

DIMENSIONAL DIAGRAMS

