

WINDSOR™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



WINDSOR™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and brass.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Mechanical

Luminaires mount directly over a junction box (by others- North America only).

L70 @25°C (77°F)

>50,000 hrs.

Suspension

Single tube combined with three diagonal decorative tubes for stabilization.

Diffusers

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

Remote Emergency


Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect

WINDSOR™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

607010 24", 12714 lms	607020 30", 15439 lms	607030 35", 22743 lms	607040 46", 30973 lms
B. CCT			
30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)	
C. FINISH			
BM Bronze Metallic Textured	MS Silver Metallic	AB Antique Brass	PB Polished Brass
SB Satin Brass	SC Satin Chrome	SN Satin Nickel	F39 Other painted finish (RAL number required)
F40 Other Non-RAL painted finish (sample chip required)			

F39 & F40 have a one time set-up charge regardless of quantity.

D. DIFFUSER

OP Opal

E. DIMMING

DA DALI Drivers **DX** DMX Drivers

F. ADDITIONAL SUSPENSION LENGTHS

S1 6" additional suspension length **S2** 12" additional suspension length **S3** 18" additional suspension length **S4** 24" additional suspension length

G. OPTIONS

RE Remote Emergency (max distance 10 ft., 120/277V) **SW** Swivel Canopy (42)

WINDSOR™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	607010	607020	607030	607040
Power	128W	150W	212W	283W
Delivered lms	12714	15439	22743	30973
LPW	100	104	107	109
Diameter (A)	24"	30"	35"	46"
Diameter (B)	5.3"	5.3"	5.3"	8.0"
Height (H)	20"	21"	21"	24"
Height (A)	3.9"	3.9"	3.9"	2.0"
Depth (D)	9"	9"	15"	18"
Weight	29lbs	33lbs	46lbs	84lbs

APPROVALS



WINDSOR™ - SUSPENDED

DIMENSIONAL DIAGRAMS

