

# WRAP PS™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# WRAP PS™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Cover

Stainless steel.

### Finish

Various as listed.

### Drivers

HPF, electronic, 120/277V (EU-240V), 0-10V, 10% dimming standard.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Main body

Steel and cast aluminium. Body retained by stainless steel screws.

### Diffuser

Opal acrylic.


### Minimum Starting Temperature

-25°C.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Ext-Wall Front/Back

# WRAP PS™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**312163** 312163  
**312217** 312217

**312211** 312211

**312213** 312213

**312215** 312215

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**MB** Metallic Bronze

**MS** Silver Metallic

**SS** Stainless Steel

OT & BL1 have a one time set-up charge regardless of quantity.

### D. OPTIONS

**RE** Remote Emergency System (max distance 25ft, 120/277V)

Dimming is not available when using RE (Remote Emergency)

## TECHNICAL DATA

### LUMINAIRE

Code	<b>312163</b>	<b>312211</b>	<b>312213</b>	<b>312215</b>	<b>312217</b>
<b>Power (LED)</b>	16W	16W	28W	28W	56W
<b>Delivered lms</b>	504	1074	1872	1782	3508
<b>LPW</b>	32	70	69	65	64
<b>Height (A)</b>	17"	26"	26"	50"	50"
<b>Width (B)</b>	11"	12"	12"	12"	12"

## APPROVALS



# WRAP PS™ - WALL SURFACE EXTERIOR

## DIMENSIONAL DIAGRAMS

