

WRAP PS™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



WRAP PS™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Cover

Stainless steel.

Finish

Various as listed.

Drivers

HPF, electronic, 120/277V (EU-240V), 0-10V, 10% dimming standard.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Main body

Steel and cast aluminium. Body retained by stainless steel screws.

Lens

Opal acrylic.


Minimum Starting Temperature

-25°C.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Wall Front/Back

WRAP PS™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

312163 312163
312217 312217

312211 312211

312213 312213

312215 312215

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

MB Metallic Bronze

MS Silver Metallic

SS Stainless Steel

OT & BL1 have a one time set-up charge regardless of quantity.

D. OPTIONS

RE Remote Emergency System (max distance 25ft, 120/277V)

Dimming is not available when using RE (Remote Emergency)

TECHNICAL DATA

LUMINAIRE

Code	312163	312211	312213	312215	312217
Power (LED)	16W	16W	28W	28W	56W
Delivered lms	504	1074	1872	1782	3508
LPW	32	70	69	65	64
Height (A)	17"	26"	26"	50"	50"
Width (B)	11"	12"	12"	12"	12"

APPROVALS



WRAP PS™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

