| Project Name: | Fixture Type: |
|---------------|---------------|
| | |
| | |
| Fixture Code: | Quantities: |



GENERAL SPECIFICATION

Cover

Stainless steel.

Finish

Various as listed.

Drivers

HPF, electronic, 120/277V (EU-240V), 0-10V, 10% dimming standard.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

OPTICS & FEATURES



Ext-Wall Front/Back

Main body

Steel and cast aluminium. Body retained by stainless steel screws.

Lens

Opal acrylic.

Minimum Starting Temperature

-25°C.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

HOW TO ORDER

A. LUMINAIRE

312163 312163 **312211** 312211 **312213** 312213 **312215** 312215

312217 312217

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. FINISH

BL Black MB Metallic Bronze MS Silver Metallic SS Stainless Steel

OT & BL1 have a one time set-up charge regardless of quantity.

D. OPTIONS

RE Remote Emergency System (max distance 25ft, 120/277V)

Dimming is not available when using RE (Remote Emergency)

TECHNICAL DATA

LUMINAIRE

| Code | 312163 | 312211 | 312213 | 312215 | 312217 | |
|---------------|--------|--------|--------|--------|--------|--|
| Power (LED) | 16W | 16W | 28W | 28W | 56W | |
| Delivered Ims | 504 | 1074 | 1872 | 1782 | 3508 | |
| LPW | 32 | 70 | 69 | 65 | 64 | |
| Height (A) | 17" | 26" | 26" | 50" | 50" | |
| Width (B) | 11" | 12" | 12" | 12" | 12" | |
| | | | | | | |

APPROVALS













DIMENSIONAL DIAGRAMS

