

## WRAP SL™ - MODERN CLASSICS EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



[betacalco.com](http://betacalco.com) | +1 416-531-9942 | [sales@betacalco.com](mailto:sales@betacalco.com)

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 5

## WRAP SL™ - MODERN CLASSICS EXTERIOR



[betacalco.com](http://betacalco.com) | +1 416-531-9942 | [sales@betacalco.com](mailto:sales@betacalco.com)

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 2 of 5

# WRAP SL™ - MODERN CLASSICS EXTERIOR

A facade light with a curved stainless steel grill adds an accent ideal for modern architecture. The grill subdues the light from the front angle and functions as a decorative accent, while light emits from all lateral sides of the luminaire, providing general illumination for the immediate area. Alternative finishes include Black, Bronze Metallic, and Silver Metallic.

## GENERAL SPECIFICATION

### Cover

Stainless steel.

### Finish

Various as listed.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Main body

Steel and cast aluminium. Body retained by stainless steel screws.

### Lens

Opal acrylic.


### Drivers

HPF, electronic, 120/277V (EU-240V), 0-10V, equal to or less than 10% dimming standard.

### Minimum Starting Temperature

-25°C.

## OPTICS & FEATURES



Ext-Wall Front/Back



General Diffuse



# WRAP SL™ - MODERN CLASSICS EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**312153** 17" Height, 16W, 243 lms  
**312227** 50" Height, 56W, 2110 lms

**312221** 26" Height, 16W, 731 lms

**312223** 26" Height, 28W, 1274 lms

**312225** 50" Height, 28W, 1064 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black Metallic Textured

**MS** Silver Metallic Textured

**BM** Bronze Metallic Textured

**SS** Stainless Steel

### D. OPTIONS

**RE** Remote Emergency System (max distance 25ft, 120/277V)

Dimming is not available when using RE (Remote Emergency)

## TECHNICAL DATA

### LUMINAIRE

Code	<b>312153</b>	<b>312221</b>	<b>312223</b>	<b>312225</b>	<b>312227</b>
<b>Power (LED)</b>	16W	16W	28W	28W	56W
<b>Delivered lms</b>	243	731	1274	1064	2110
<b>LPW</b>	16	48	47	39	39
<b>Height (A)</b>	17"	26"	26"	50"	50"
<b>Width (B)</b>	11"	12"	12"	12"	12"

### FINISH



Black Metallic Textured



Silver Metallic Textured



Bronze Metallic Textured



Stainless Steel

### APPROVALS



# WRAP SL™ - MODERN CLASSICS EXTERIOR

## DIMENSIONAL DIAGRAMS

