

XACARA CL SQ™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



XACARA CL SQ™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Gimbal

Fully articulating on two axes.

Reflectors

Highly reflective, specular finish, vacuum plated.

Power cable

Silver braided.

Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Note

Photometric testing performed using LM79 procedures.

Array housings

Die cast aluminium.

Suspension

Two or four cables, fully adjustable.

Protective lens

Clear glass.

Finish

Powder coated, as specified.

L70 @25°C (77°F)

> 60,000 hrs.

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

XACARA CL SQ™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

501220 50 1220

501240 50 1240

B. CCT/CRI

30A 3000K (min 80 CRI)

30B 3000K (min 90 CRI)

35A 3500K (min 80 CRI)

35B 3500K (min 90 CRI)

40A 4000K (min 80 CRI)

40B 4000K (min 90 CRI)

C. REFLECTOR

ME Medium 36°

XW Extra wide 70°

D. FINISH

BL Black

MS Silver Metallic

WH White

TECHNICAL DATA

LUMINAIRE

| | | |
|----------------------|---------------|---------------|
| Code | 501220 | 501240 |
| Power (LED) | 2 x 26W | 4 x 26W |
| Delivered lms | 2 x 2085 | 4 x 2085 |
| LPW | 80 | 80 |
| CBCP | 4104 | 4104 |

APPROVALS



XACARA CL SQ™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

