

# XACARA CL SQ™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA CL SQ™ - CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium.

### Gimbal

Fully articulating on two axes.

### Reflectors

Highly reflective, specular finish, vacuum plated.

### Power cable

Silver braided.

### Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Note

*Photometric testing performed using LM79 procedures.*

### Array housings

Die cast aluminium.

### Suspension

Two or four cables, fully adjustable.

### Protective lens

Clear glass.

### Finish

Powder coated, as specified.

### L70 @25°C (77°F)

> 60,000 hrs.

### Approvals

Damp Location (Indoor use only).

## OPTICS & FEATURES



Ceiling

# XACARA CL SQ™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**501220** 50 1220

**501240** 50 1240

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. REFLECTOR

**ME** Medium 36°

**XW** Extra wide 70°

### D. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>501220</b>	<b>501240</b>
<b>Power (LED)</b>	2 x 26W	4 x 26W
<b>Delivered lms</b>	2 x 2085	4 x 2085
<b>LPW</b>	80	80
<b>CBCP</b>	4104	4104

## APPROVALS



# XACARA CL SQ™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

