

# XACARA L™ - DIRECT/INDIRECT

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA L™ - DIRECT/INDIRECT

## GENERAL SPECIFICATION

### Body

Die cast aluminum and steel.

### Finish

Powder coated.

### Suspension

Three or four stainless steel aircraft cables.

### Power cable

Silver braided.

### Reflectors

Aluminum, specular finish with vertical facets.

### Decorative disc (optional)

6mm/14" green tint acrylic (faux glass) with a polished edge and a etched face.

### Drivers

120/277V (EU-240V) electronic with 0-10V dimming (10%).

### L70@25°C

> 60,000 hrs.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


### Approvals

Damp Location (Indoor use only).

### Note

*Photometric testing performed using LM79 procedures.*

## OPTICS & FEATURES



Suspended Direct/Indirect

# XACARA L™ - DIRECT/INDIRECT

## HOW TO ORDER

### A. LUMINAIRE

**506750** 120W (4 LEDs down, 1 up),  
9536 lms Direct, 1843 lms Indirect

**506755** 140W (5 LEDs down, 1 up),  
11899 lms Direct, 1843 lms Indirect

**506760** 165W (6 LEDs down, 1 up),  
14246 lms Direct, 1843 lms Indirect

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

### D. OPTIONS

**BT** Bezel Trim (28" Diam)

**DD** Decorative Disc (acrylic)

**DA** DALI Dimming (10%)

**SS** Separate Switching

## TECHNICAL DATA

### LUMINAIRE

Code	506750	506755	506760
Power	120W (4 LEDs down, 1 up)	140W (5 LEDs down, 1 up)	165W (6 LEDs down, 1 up)
Direct lms	9536	11899	14246
Indirect lms	1843	1843	1843
LPW	100	101	102
Weight	30lb	30lb	30lb

## APPROVALS



DAMP  
LOCATION



IP20



# XACARA L™ - DIRECT/INDIRECT

## DIMENSIONAL DIAGRAMS

