

XACARA L™ - DIRECT/INDIRECT

Project Name:

Fixture Type:

Fixture Code:

Quantities:



XACARA L™ - DIRECT/INDIRECT

GENERAL SPECIFICATION

Body

Die cast aluminum and steel.

Finish

Powder coated.

Suspension

Three or four stainless steel aircraft cables.

Power cable

Silver braided.

Reflectors

Aluminum, specular finish with vertical facets.

Decorative disc (optional)

6mm/1/4" green tint acrylic (faux glass) with a polished edge and a etched face.

Drivers

120/277V (EU-240V) electronic with 0-10V dimming (10%).

L70@25°C

> 60,000 hrs.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

Note

Photometric testing performed using LM79 procedures.

OPTICS & FEATURES



Suspended Direct/Indirect

XACARA L™ - DIRECT/INDIRECT

HOW TO ORDER

A. LUMINAIRE

506750 120W (4 LEDs down, 1 up),
9536 lms Direct, 1843 lms Indirect

506755 140W (5 LEDs down, 1 up),
11899 lms Direct, 1843 lms Indirect

506760 165W (6 LEDs down, 1 up),
14246 lms Direct, 1843 lms Indirect

B. CCT/CRI

30A 3000K (min 80 CRI)

30B 3000K (min 90 CRI)

35A 3500K (min 80 CRI)

35B 3500K (min 90 CRI)

40A 4000K (min 80 CRI)

40B 4000K (min 90 CRI)

C. FINISH

BL Black

MS Silver Metallic

WH White

D. OPTIONS

BT Bezel Trim (28" Diam)

DD Decorative Disc (acrylic)

DA DALI Dimming (10%)

SS Separate Switching

TECHNICAL DATA

LUMINAIRE

Code	506750	506755	506760
Power	120W (4 LEDs down, 1 up)	140W (5 LEDs down, 1 up)	165W (6 LEDs down, 1 up)
Direct lms	9536	11899	14246
Indirect lms	1843	1843	1843
LPW	100	101	102
Weight	30lb	30lb	30lb

APPROVALS



DAMP
LOCATION



IP20



XACARA L™ - DIRECT/INDIRECT

DIMENSIONAL DIAGRAMS

