

# XACARA L INDIRECT™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



## XACARA L INDIRECT™ - SUSPENDED



# XACARA L INDIRECT™ - SUSPENDED

## GENERAL SPECIFICATION

### Body

Die cast aluminium and steel.

### Suspension

Two polished chrome plated tubes or three stainless steel cables.

### Reflectors

Aluminium, specular finish with vertical facets.

### Drivers

HPF electronic 120-277V (EU-240V), 0-10V dimming standard (10%).

### Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

### Mechanical

Luminaires mount directly over a junction box (not supplied).

### Approvals

Damp Location (Indoor use only).

### Finish

White powder coated.

### Visible power cable

Silver braided.

### Dust cover

Clear polycarbonate.

### Emergency systems

### Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Note

*Photometric testing performed using LM79 procedures.*

## OPTICS & FEATURES



Suspended Indirect

## XACARA L INDIRECT™ - SUSPENDED

## HOW TO ORDER

## A. LUMINAIRE

**503520** 503520

**503620** 503620

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. SUSPENSION

### TS Tube Suspension

## CS Cable Suspension

## D. OPTIONS

**RE** Remote Emergency (max distance 15ft. Not available with DALI or 347V)

**DA** DALI Dimming (10%) (Not available with RE or 347V)

**3** 347V (not available with DALI or RE)

## TECHNICAL DATA

## LUMINAIRE

<b>Code</b>	<b>503520</b>	<b>503620</b>
<b>Power (LED)</b>	140W	175W
<b>Delivered lms</b>	13631	17009
<b>LPW</b>	103	103

## APPROVALS

DAMP  
LOCATION

IP20

XACARA L INDIRECT™ - SUSPENDED

DIMENSIONAL DIAGRAMS

