XACARA L INDIRECT™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

XACARA L INDIRECT™ - SUSPENDED



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

XACARA L INDIRECT™ - SUSPENDED

GENERAL SPECIFICATION

Body
Die cast aluminium and steel.

Suspension
Two polished chrome plated tubes or three stainless steel cables.

Reflectors
Aluminium, specular finish with vertical facets.

Drivers
HPF electronic 120-277V (EU-240V), 0-10V dimming standard (10%).

Integral
Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

Mechanical
Luminaires mount directly over a junction box (not supplied).

Approvals
Damp Location (Indoor use only).

Finish
White powder coated.

Visible power cable
Silver braided.

Dust cover
Clear polycarbonate.

Emergency systems

Remote
Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens
Delivered lumens & LPW based on 3000K (min 80 CRI).

Note

Photometric testing performed using LM79 procedures.

OPTICS & FEATURES



Suspended Indirect

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

XACARA L INDIRECT™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

503520 503520

503620 503620

B. CCT/CRI

30A 3000K (min 80 CRI)

30B 3000K (min 90 CRI)

35A 3500K (min 80 CRI)

35B 3500K (min 90 CRI)

40A 4000K (min 80 CRI)

40B 4000K (min 90 CRI)

C. SUSPENSION

TS Tube Suspension

CS Cable Suspension

D. OPTIONS

RE Remote Emergency (max distance 15ft. Not available with DALI or 347V)

DA DALI Dimming (10%) (Not available with RE or 347V)

3 347V (not available with DALI or RE)

TECHNICAL DATA

LUMINAIRE


Code	503520	503620
Power (LED)	140W	175W
Delivered lms	13631	17009
LPW	103	103


APPROVALS

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

XACARA L INDIRECT™ - SUSPENDED

DIMENSIONAL DIAGRAMS





© 2026 Beta-Calco Inc. Specifications are subject to change without notice