

# XACARA L REFLEKTOR™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



## XACARA L REFLEKTOR™ - SUSPENDED



# XACARA L REFLEKTOR™ - SUSPENDED

## GENERAL SPECIFICATION

### Body

Die cast aluminium and steel.

### Suspension

Two polished chrome plated tubes or stainless steel cables.

### Reflectors

Aluminium, specular finish with vertical facets.

### Drivers

HPF electronic 120-277V (EU-240V), 0-10V, 10% dimming.

### Emergency systems

#### Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

#### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

#### Note

*Photometric testing performed using LM79 procedures.*

## OPTICS & FEATURES



Suspended Direct/Indirect

### Finish

White powder coated.

### Power cable

Silver braided.

### LED protection

Clear lense.

### Dust cover

Clear polycarbonate.

### Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

### Mechanical

Luminaires mount directly over a junction box (not supplied).

### Approvals

Damp Location (Indoor use only).

# XACARA L REFLEKTOR™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**502520** 502520

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. SUSPENSION

**TS** Tube Suspension

**CS** Cable Suspension

### D. OPTIONS

**DA** DALI Dimming - 10% (not available with 347V)

**RE** Remote Emergency (not available with DALI or 347V)

**3** 347V (not available with DALI or RE)

**SS** Separate Switching (in combination with UM, 0-10V dimming only)

**UH** Uplight Hole (6" dia hole in main reflector provides upwards illumination)

**UM** Uplight Module (1x28W Xacara, LED array same as specified in main housing)

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>502520</b>
<b>Power (LED)</b>	120W
<b>Delivered lms</b>	9187
<b>LPW</b>	77

## APPROVALS



# XACARA L REFLEKTOR™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

