




# XACARA L™


## FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

### 1 DESCRIPTION

The raw design delivers primal functionality in light performance and to interior aesthetics. Choose between 4, 5, and 6 LED modules to optimize light levels according to the application. **XACARA** packs light outputs suitable for industrial settings, warehouses, and superstores. The fixture comes in 3 colors, White, Black and Silver Metallic Textured, providing a cohesive look that can match your space. There are also options to include additional decorative features such as bezel trims, decorative discs and ceiling mount options.

### 2 OPTICS & FEATURES



### 3 APPROVALS



### 4 GENERAL SPECIFICATION

#### BODY

Die cast aluminum and steel.

#### FINISH

Powder coated.

**SUSPENSION**

Three or four stainless steel aircraft cables.

**DRIVERS**

120/277V (EU-240V) electronic with 0-10V dimming (10%). The driver is integral to the fixture housing.

**REFLECTORS**

Aluminum, specular finish with vertical facets.

**INTEGRAL**

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency luminaires have a 50mm/2" extended ballast housing. Not available with a 347V supply.

**REPORTED L70 @25°C(77°F)**

> 60,000 hrs.

**NOTE**

Photometric testing performed using LM79 procedures.

**SUSTAINABILITY**

Designed for on-site LED board, driver, and optic replacement. Contact the factory for maintenance documentation.

**5 DESIGN OPTIONS**

**FINISH**



White



Black



Silver  
Metallic  
Textured

**POWER CABLE**

Silver braided.

**DECORATIVE DISC (OPTIONAL)**

6mm/0.25" green tint acrylic (faux glass) with a polished edge and a etched face.

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**REMOTE**

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

**APPROVALS**

Damp Rated.

**SENSORS**

Consult factory regarding sensor compatibility.



**8** DIMENSIONAL DIAGRAMS

