

XACARA RD™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



XACARA RD™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Gimbal

Fully articulating on two axes.

Reflectors

Medium and wide beam. Highly reflective, specular finish, vacuum plated.

Power cable

Silver braided.

Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Note

Photometric testing performed using LM79 procedures.

Array housings

Die cast aluminium.

Suspension

Three cables, fully adjustable.

Protective lens

Clear glass.

Finish

Powder coated, as specified.

L70 @25°C (77°F)

> 60,000 hrs.

Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



Suspended Direct



36°



70°



XACARA RD™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

501030 50 1030

501060 50 1060

B. CCT/CRI

30A 3000K (min 80 CRI)

30B 3000K (min 90 CRI)

35A 3500K (min 80 CRI)

35B 3500K (min 90 CRI)

40A 4000K (min 80 CRI)

40B 4000K (min 90 CRI)

C. REFLECTOR

ME Medium 36°

XW Extra Wide 70°

D. FINISH

BL Black

MS Silver Metallic

WH White

TECHNICAL DATA

LUMINAIRE

Code	501030	501060
Power (LED)	3 x 26W	6 x 26W
Delivered lms	3 x 2085	6 x 2085
LPW	80	80

APPROVALS



DAMP
LOCATION



IP20



XACARA RD™ - SUSPENDED

DIMENSIONAL DIAGRAMS

