

# XACARA RD™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA RD™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium.

### Gimbal

Fully articulating on two axes.

### Reflectors

Medium and wide beam. Highly reflective, specular finish, vacuum plated.

### Power cable

Silver braided.

### Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Note

*Photometric testing performed using LM79 procedures.*

### Array housings

Die cast aluminium.

### Suspension

Three cables, fully adjustable.

### Protective lens

Clear glass.

### Finish

Powder coated, as specified.

### L70 @25°C (77°F)

> 60,000 hrs.

### Approvals

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Suspended Direct



36°



70°



# XACARA RD™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**501030** 50 1030

**501060** 50 1060

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. REFLECTOR

**ME** Medium 36°

**XW** Extra Wide 70°

### D. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

## TECHNICAL DATA

### LUMINAIRE

Code	501030	501060
Power (LED)	3 x 26W	6 x 26W
Delivered lms	3 x 2085	6 x 2085
LPW	80	80

## APPROVALS



DAMP  
LOCATION



IP20

# XACARA RD™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

