

# XACARA S™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA S™ - SUSPENDED

## GENERAL SPECIFICATION

### Body

Die cast aluminum.

### Finish

Powder coated.

### Suspension

Single stainless steel aircraft cable or steel tube.

### Power cable

Clear with silver wires.

### Reflectors

Highly reflective, specular finish, vacuum plated.

### Drivers

HPF electronic, 120/277V (EU-240V).

### L70 @25°C (77°F)

> 60,000 hrs.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Approvals

Damp Location (Indoor use only).


### Note

*Photometric testing performed using LM79 procedures.*


## OPTICS & FEATURES



Suspended Direct



28°



47°



# XACARA S™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**511100** 38W

### B. CCT/CRI ( BRIDGELUX )

**B430A** 3000K, 80 CRI, 3045 lms

**B430B** 3000K, 90 CRI, 2471 lms

**B435A** 3500K, 80 CRI, 3133 lms

**B435B** 3500K, 90 CRI, 2674 lms

**B440A** 4000K, 80 CRI, 3185 lms

**B440B** 4000K, 90 CRI, 2686 lms

### C. REFLECTOR

**ME** Medium 28°

**WD** Extra wide 47°

### D. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

### E. SUSPENSION

**CS** Cable Suspension

**TS3** Tube 18"

**TS4** Tube 24"

**TS5** Tube 30"

**TS6** Tube 36"

**TS7** Tube 42"

**TS8** Tube 48"

### F. DIMMING

**D1** 0-10V Dimming (1%)

**D2** 0-10V Dimming (0.1%)

**DL** DALI Dimming (1%)

**DA** DALI Dimming (0.1%)

**L1** Lutron L3DA3W Hi-Lume 1%

**L3** Lutron L3DAE Hi-Lume 1%  
EcoSystem



# XACARA S™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

|             |        |
|-------------|--------|
| Code        | 511100 |
| Power (LED) | 38W    |
| LPW         | 83     |

---

### CCT/CRI

| Code          | B430A | B430B | B435A | B435B | B440A | B440B |
|---------------|-------|-------|-------|-------|-------|-------|
| CCT           | 3000K | 3000K | 3500K | 3500K | 4000K | 4000K |
| CRI           | 80    | 90    | 80    | 90    | 80    | 90    |
| Delivered lms | 3045  | 2471  | 3133  | 2674  | 3185  | 2686  |
| LPW           | 80    | 65    | 82    | 70    | 83    | 70    |

---

## APPROVALS



DAMP  
LOCATION



IP20



# XACARA S™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

