

# XACARA SM™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA SM™ - WALL SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium (extruded).

### Array housings

Die cast aluminium.

### Gimbal

Fully articulating on two axes.

### Reflectors

Medium and wide beam. Highly reflective, specular finish, vacuum plated.

### Protective lens

Clear glass.

### Mounting

Mounts directly over a 2"x3" switch box (by others).

### Orientation

Ceiling or wall. May be inverted.

### Visible cable

Silver.

### Finish

Powder coated, as specified.

### Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming.


### L70 @25°C (77°F)

> 60,000 hrs.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Wall

# XACARA SM™ - WALL SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**502210** 502210

**502215** 502215

**502220** 502220

**502230** 502230

**502240** 502240

### B. CCT/CRI

**30A** 3000K (min 80 CRI)

**30B** 3000K (min 90 CRI)

**35A** 3500K (min 80 CRI)

**35B** 3500K (min 90 CRI)

**40A** 4000K (min 80 CRI)

**40B** 4000K (min 90 CRI)

### C. REFLECTORS

**ME** Medium 36°

**XW** Extra wide 70°

### D. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

## TECHNICAL DATA

### LUMINAIRE

Code	502210	502215	502220	502230	502240
Power (LED)	1 x 26W	1 x 26W	2 x 26W	3 x 26W	4 x 26W
Delivered lms	1 x 2085	1 x 2085	2 x 2085	3 x 2085	4 x 2085
LPW	80	80	80	80	80

## APPROVALS



DAMP  
LOCATION



IP20



# XACARA SM™ - WALL SURFACE

## DIMENSIONAL DIAGRAMS

