

XACARA SM™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



XACARA SM™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminium (extruded).

Array housings

Die cast aluminium.

Gimbal

Fully articulating on two axes.

Reflectors

Medium and wide beam. Highly reflective, specular finish, vacuum plated.

Protective lens

Clear glass.

Mounting

Mounts directly over a 2"x3" switch box (by others).

Orientation

Ceiling or wall. May be inverted.

Visible cable

Silver.

Finish

Powder coated, as specified.

Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming.


L70 @25°C (77°F)

> 60,000 hrs.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall

XACARA SM™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

502210 502210

502215 502215

502220 502220

502230 502230

502240 502240

B. CCT/CRI

30A 3000K (min 80 CRI)

30B 3000K (min 90 CRI)

35A 3500K (min 80 CRI)

35B 3500K (min 90 CRI)

40A 4000K (min 80 CRI)

40B 4000K (min 90 CRI)

C. REFLECTORS

ME Medium 36°

XW Extra wide 70°

D. FINISH

BL Black

MS Silver Metallic

WH White

TECHNICAL DATA

LUMINAIRE

| Code | 502210 | 502215 | 502220 | 502230 | 502240 |
|---------------|----------|----------|----------|----------|----------|
| Power (LED) | 1 x 26W | 1 x 26W | 2 x 26W | 3 x 26W | 4 x 26W |
| Delivered lms | 1 x 2085 | 1 x 2085 | 2 x 2085 | 3 x 2085 | 4 x 2085 |
| LPW | 80 | 80 | 80 | 80 | 80 |

APPROVALS



XACARA SM™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

