

# XACARA TIROS™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA TIROS™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium (extruded).

### Array housings

Die cast aluminium.

### Gimbal

Fully articulating on two axes.

### Suspension

Two cables, fully adjustable.

### Reflectors

Highly reflective, specular finish, vacuum plated.

### Protective lens

Clear glass. Supplied with 26W fixtures only.

### Power cable

Silver braided.

### Finish

Silver Metallic powder coated.

### Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

### L70 @25°C (77°F)

> 60,000 hrs.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Approvals

Damp Location (Indoor use only).

### Note

*Photometric testing performed using LM79 procedures.*

## MOUNTING & OPTICS



Suspended Direct

26W-36°

26W-70°

38W-28°

38W-47°



# XACARA TIROS™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**510510** 510510

**510560** 510560

**510520** 510520

**510580** 510580

**510530** 510530

**510540** 510540

### B. BRIDGELUX LED

**LA**

**LE**

**LI**

**LB**

**LF** 4000K, 90 CRI, 1820 lms

**LJ** 3500K, 90 CRI, 2674 lms

**LC**

**LG** 3000K, 80 CRI, 3045 lms

**LK** 4000K, 80 CRI, 3185 lms

**LD** 3500K, 90 CRI, 1770 lms

**LH**

**LL** 4000K, 90 CRI, 2686 lms

### C. REFLECTORS

**R1** Medium 36° (Bridgelux-26W)

**R2** Extra Wide 70° (Bridgelux-26W)

**R3** Medium 28° (Bridgelux-38W)

**R4** Wide 47° (Bridgelux-38W)

Reflectors **MUST** be ordered

### D. DIMMING OPTIONS (FOR 1-4 HEAD FIXTURES ONLY)

**D1** 0-10V Dimming 1%

**D2** 0-10V Dimming 0.1%

**DL** DALI Dimming 1%

**DA** DALI Dimming 0.1%

**L1** Lutron L3DA3W Hi-Lume 1%

**L2** Lutron LDE1 Hi-Lume 1% - H EcoSystem

**L3** Lutron L3DAE Hi-Lume 1% EcoSystem

## TECHNICAL DATA

### LUMINAIRE

Code	<b>510510</b>	<b>510520</b>	<b>510530</b>	<b>510540</b>	<b>510560</b>	<b>510580</b>
Type	1 spotlight head	2 spotlight heads	3 spotlight heads	4 spotlight heads	6 spotlight heads	8 spotlight heads

### LED

Code	<b>LA</b>	<b>LB</b>	<b>LC</b>	<b>LD</b>	<b>LE</b>	<b>LF</b>
Power (LED)	26W	26W	26W	26W	26W	26W
CCT	3000K	3000K	3500K	3500K	4000K	4000K
CRI	80	90	80	90	80	90
Dimensions	A	A	A	A	A	A
Delivered lms	2085	1689	2127	1770	2169	1820
LPW	80	65	81	68	83	70
CBCP	4104	3324	4186	3483	4268	3581

Code	<b>LG</b>	<b>LH</b>	<b>LI</b>	<b>LJ</b>	<b>LK</b>	<b>LL</b>
Power (LED)	38W	38W	38W	38W	38W	38W
CCT	3000K	3000K	3500K	3500K	4000K	4000K
CRI	80	90	80	90	80	90
Dimensions	B	B	B	B	B	B
Delivered lms	3045	2471	3133	2674	3185	2686
LPW	80	65	82	70	83	70
CBCP	6087	4938	6264	5344	6367	5369

# XACARA TIROS™ - SUSPENDED

## APPROVALS



DAMP  
LOCATION



IP20



# XACARA TIROS™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

