

# XACARA™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# XACARA™ - SUSPENDED

## GENERAL SPECIFICATION

### Body

Die cast aluminum.

### Finish

Powder coated.

### Suspension

Single stainless steel aircraft cable or steel tube.

### Power cable

Clear with silver wires.

### Reflectors

Aluminum, specular finish with multiple facets.

### Protective lens

Clear glass.

### Drivers

HPF electronic, 120/277V (EU-240V).

### L70 @25°C (77°F)

> 60,000 hrs.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Approvals

Damp Location (Indoor use only).

### Note

*Photometric testing performed using LM79 procedures.*

## MOUNTING & OPTICS



Suspended Direct

36°

70°

# XACARA™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**501000** 11W, 862

**501002** 15W, 1143

**501004** 26W, 2085

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. REFLECTOR

**ME** Medium 36°

**XW** Extra wide 70°

### D. FINISH

**BL** Black

**MS** Silver Metallic

**WH** White

### E. SUSPENSION

**CS** Cable suspension

**TS3** Tube 18"

**TS4** Tube 24"

**TS5** Tube 30"

**TS6** Tube 36"

**TS7** Tube 42"

**TS8** Tube 48"

### F. DIMMING

**D1** 0-10V Dimming (1%)

**D2** 0-10V Dimming (0.1%)

**DL** DALI Dimming (1%)

**DA** DALI Dimming (0.1%)

**L1** Lutron L3DA3W Hi-Lume 1%

**L3** Lutron L3DAE Hi-Lume 1%  
EcoSystem



# XACARA™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

Code	501000	501002	501004
Power (LED)	11W	15W	26W
Delivered lms	862	1143	2085
LPW	78	76	80

---

## APPROVALS



# XACARA™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

