

XACARA™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



XACARA™ - SUSPENDED

GENERAL SPECIFICATION

Body

Die cast aluminum.

Finish

Powder coated.

Suspension

Single stainless steel aircraft cable or steel tube.

Power cable

Clear with silver wires.

Reflectors

Aluminum, specular finish with multiple facets.

Protective lens

Clear glass.

Drivers

HPF electronic, 120/277V (EU-240V).

L70 @25°C (77°F)

> 60,000 hrs.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

Note

Photometric testing performed using LM79 procedures.

OPTICS & FEATURES



Suspended Direct

36°

70°

XACARA™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

501000 11W, 862

501002 15W, 1143

501004 26W, 2085

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. REFLECTOR

ME Medium 36°

XW Extra wide 70°

D. FINISH

BL Black

MS Silver Metallic

WH White

E. SUSPENSION

CS Cable suspension

TS3 Tube 18"

TS4 Tube 24"

TS5 Tube 30"

TS6 Tube 36"

TS7 Tube 42"

TS8 Tube 48"

F. DIMMING

D1 0-10V Dimming (1%)

D2 0-10V Dimming (0.1%)

DL DALI Dimming (1%)

DA DALI Dimming (0.1%)

L1 Lutron L3DA3W Hi-Lume 1%

L3 Lutron L3DAE Hi-Lume 1%
EcoSystem



XACARA™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	501000	501002	501004
Power (LED)	11W	15W	26W
Delivered lms	862	1143	2085
LPW	78	76	80

APPROVALS



XACARA™ - SUSPENDED

DIMENSIONAL DIAGRAMS

