

## ZEDOS PM™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



[betacalco.com](http://betacalco.com) | +1 416-531-9942 | [sales@betacalco.com](mailto:sales@betacalco.com)

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 4

# ZEDOS PM™ - WALL OR CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Finish**

Powder coated or plated as listed.

**Lens**

Opal polycarbonate.

**Drivers**

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

**Luminaire orientation**

Ceiling or wall.

**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI). **Approvals**

Damp Location (Indoor use only).

## OPTICS & FEATURES



Ceiling



# ZEDOS PM™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**681680** 681680

**682180** 682180

**682183** 682183

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MS** Silver Metallic

**SN** Satin Nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish  
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>681680</b>	<b>682180</b>	<b>682183</b>
<b>Power (LED)</b>	28W	28W	36W
<b>Delivered lms</b>	1894	2002	2638
<b>LPW</b>	68	71	73
<b>Diameter (A)</b>	15.7"	20.8"	20.8"
<b>Depth (D)</b>	4"	4"	4"
<b>Weight</b>	4lb	5.5lb	5.5lb

## APPROVALS



DAMP  
LOCATION



IP20



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 3 of 4

## ZEDOS PM™ - WALL OR CEILING SURFACE

### DIMENSIONAL DIAGRAMS

