

# ZEDOS PM™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ZEDOS PM™ - WALL OR CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Powder coated or plated as listed.

### Diffusers

Opal polycarbonate.

### Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

### Luminaire orientation

Ceiling or wall.

### Mechanical

Mounts directly to a junction box (by others - North America only).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Approvals

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling

# ZEDOS PM™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**681680** 681680

**682180** 682180

**682183** 682183

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MS** Silver Metallic

**SN** Satin Nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish  
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>681680</b>	<b>682180</b>	<b>682183</b>
Power (LED)	28W	28W	36W
Delivered lms	1894	2002	2638
LPW	68	71	73
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

## APPROVALS



# ZEDOS PM™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

