Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Lens

Finish Powder coated or plated as listed.

Steel and aluminum.

Drivers

Opal polycarbonate.

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Mechanical

Ceiling or wall.

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Approvals

Delivered lumens & LPW based on 3000K (min 80 CRI).

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

HOW TO ORDER

A. LUMINAIRE

681680 681680 **682180** 682180 **682183** 682183

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White MS Silver Metallic SN Satin Nickel OT Other painted finish (RAL number

required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	681680	682180	682183
Power (LED)	28W	28W	36W
Delivered Ims	1894	2002	2638
LPW	68	71	73
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

APPROVALS













DIMENSIONAL DIAGRAMS

