

ZEDOS PM™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



ZEDOS PM™ - WALL OR CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Powder coated or plated as listed.

Diffusers

Opal polycarbonate.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling

ZEDOS PM™ - WALL OR CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

681680 681680	682180 682180	682183 682183	
B. CCT			
30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)	
C. FINISH			
WH White	MS Silver Metallic	SN Satin Nickel	OT Other painted finish (RAL number required)
F40 Other Non-RAL painted finish (sample chip required)			

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	681680	682180	682183
Power (LED)	28W	28W	36W
Delivered lms	1894	2002	2638
LPW	68	71	73
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

APPROVALS



ZEDOS PM™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

