

ZEDOS SR™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 4

ZEDOS SR™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Powder coated or plated as listed.

Lens

Opal polycarbonate.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall.

Mechanical

Mounts directly to a junction box (by others - North America only).


Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI). Damp Location (Indoor use only).


Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



Ceiling



Direct



ZEDOS SR™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

681660 15.7", 28W, 2056 lms **682160** 20.8", 28W, 2167 lms **682163** 20.8", 36W, 2856 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White **MS** Silver Metallic **SN** Satin Nickel **OT** Other painted finish (RAL number required)

F40 Other Non-RAL painted finish
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	681660	682160	682163
Power (LED)	28W	28W	36W
Delivered lms	2056	2167	2856
LPW	73	77	80
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

APPROVALS



DAMP
LOCATION



IP20



ZEDOS SR™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

