| Fixture Code: | Quantities: |
|---------------|---------------|
| | |
| Project Name: | Fixture Type: |



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Lens

Opal polycarbonate.

Luminaire orientation

Ceiling or wall.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Powder coated or plated as listed.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES





Direct

HOW TO ORDER

A. LUMINAIRE

681660 15.7", 28W, 2056 lms **682160** 20.8", 28W, 2167 lms **682163** 20.8", 36W, 2856 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White **MS** Silver Metallic **SN** Satin Nickel **OT** Other painted finish (RAL number

required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

| Code | 681660 | 682160 | 682163 |
|---------------|--------|--------|--------|
| Power (LED) | 28W | 28W | 36W |
| Delivered Ims | 2056 | 2167 | 2856 |
| LPW | 73 | 77 | 80 |
| Diameter (A) | 15.7" | 20.8" | 20.8" |
| Depth (D) | 4" | 4" | 4" |
| Weight | 4lb | 5.5lb | 5.5lb |

APPROVALS













DIMENSIONAL DIAGRAMS

