

# ZEDOS SR™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ZEDOS SR™ - CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Powder coated or plated as listed.

### Diffusers

Opal polycarbonate.

### Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

### Luminaire orientation

Ceiling or wall.

### Mechanical

Mounts directly to a junction box (by others - North America only).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


### Approvals

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling



Direct

# ZEDOS SR™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**681660** 15.7", 28W, 2056 lms

**682160** 20.8", 28W, 2167 lms

**682163** 20.8", 36W, 2856 lms

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MS** Silver Metallic

**SN** Satin Nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish  
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

| Code          | <b>681660</b> | <b>682160</b> | <b>682163</b> |
|---------------|---------------|---------------|---------------|
| Power (LED)   | 28W           | 28W           | 36W           |
| Delivered lms | 2056          | 2167          | 2856          |
| LPW           | 73            | 77            | 80            |
| Diameter (A)  | 15.7"         | 20.8"         | 20.8"         |
| Depth (D)     | 4"            | 4"            | 4"            |
| Weight        | 4lb           | 5.5lb         | 5.5lb         |

## APPROVALS



# ZEDOS SR™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

