

ZEDOS SR™ - CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



ZEDOS SR™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Powder coated or plated as listed.

Diffusers

Opal polycarbonate.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



Ceiling



Direct



ZEDOS SR™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

681660 15.7", 28W, 2056 lms

682160 20.8", 28W, 2167 lms

682163 20.8", 36W, 2856 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MS Silver Metallic

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	681660	682160	682163
Power (LED)	28W	28W	36W
Delivered lms	2056	2167	2856
LPW	73	77	80
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

APPROVALS



ZEDOS SR™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

